

**Product Code****Description****Static Clean ( Blanco y transparente)**

Gloss clear static cling phthalatefree vinyl.

Printing methods: solvent based screen printing, offset UV.

Material without adhesive.

For use in advertising specialties such as retail window signage, promotional displays and holiday decorations.

ATTENTION: to reach a good printability the material must be printed within three months from its receipt.

Application to paintwork : owing to the wide variation in paint quality material should be fully tested.

**Technical Data****FACE MATERIAL**

Type	Static plasticised vinyl
Colour and Finish	Clear, Gloss
Weight	230g/m <sup>2</sup>
Thickness	180µ

**ADHESIVE**

Reference	--
Type	--
Min. Appl. Temp.	--
Service Temp.	--
Shear	--h
Tack	-
Ultimate Adhesion	-

**RELEASE BACKING**

Type	Gloss cast coated board
Colour and Finish	White
Weight	180g/m <sup>2</sup>
Thickness	225µ

**CHEMICAL RESISTANCE**

Detergent	No effect (24 Hrs)
Gasoline	Poor (1 Hrs)
SAE20 Motoroil	Poor (24 Hrs)
10% HCl	Poor (10 min)
10% NH4OH	Poor (10 min)

**Storage**

The material must be stored at a temperature of 22°C +/- 2°C and 50% +/- 5% of Relative Humidity. Do not expose to direct sun light.

The area must be dry and clean. Please keep the material in the original packaging when not use in order to protect it from dust and contaminations.

All values presented in this data sheet are typical. The information is given in good faith but without warranty. Purchasers should carefully assess the suitability of the product for their own specific application. All specifications are subject to change without prior notice.

